

Single Chamber Water Baths

Provide for precise and constant temperature and auxiliary heating in colleges, industrial, mining enterprises, and scientific research departments.

Features

- Microprocessor control with timing function
- Digital display
- Audible and visible alarm for over heat



Specifications

SDK Series

Model	SDK-12	SDK-22	SDK-30	SMP-501A
Material	Stainless Steel			
Temperature Controller	Programmable			
Temperature Range	RT+5 to 100°C			
Temperature Stability	±0.5°C			±0.2°C
Over Heat Alarm	Yes			
Display Resolution	0.1°C			
Capacity	12L	22L	30L	14.5L
Chambers	One			
Interior Dimension (WxDxH)	300 x 240 x 160 mm	450 x 300 x 160 mm	600 x 300 x 160 mm	240 x 170 x 200 mm
Exterior Dimension (WxDxH)	460 x 280 x 190 mm	610 x 340 x 190 mm	760 x 340 x 190 mm	305 x 480 x 470 mm
Timing Range	1 to 999 minutes			
Power Supply	220V 50HZ			
Power Consumption	400W	600W	1000W	2000W
Shipping Dimension	21 x 14 x 13.5 inch 530 x 350 x 340 mm	27.5 x 17 x 15 inch 700 x 435 x 375 mm	22 x 14 x 16 inch 555 x 350 x 395 mm	20.5 x 15 x 22 inch 520 x 380 x 550 mm
Shipping Weight	20 lbs / 9 kg	24.7 lbs / 11.2 kg	22.7 lbs / 10.3 kg	31.3 lbs / 14.2 kg

Single Chamber Circulating Baths

Provide for precise and constant temperature and auxiliary heating in colleges, industrial, mining enterprises, and scientific research departments.

Features

- Microprocessor control with timing function
- Digital display
- Audible and visible alarm for over temperature



DKB-22



DKB-30



TS-27